



ROLLING TOWER

www.totalaccesssolutions.com.au



SINGLE WIDTH 5400

Altrex offers a single-width folding tower which is particularly suited to work indoors. It has a base measurement of 0.75 x 1.85 meter. This scaffold is particularly suited to work in small spaces.

- Because this single width folding tower frame has one rung less than the normal frames, it can be driven through standard door opening without having to be dismantled
- The wheels with a diameter of 125 mm with the anti-slip surface are particularly suited for interior work
- By plating a guardrail frame on the 6-rung folding frame one can easily increase the working height to 4 metres
- It goes without saying that these folding sections can also be used in the single width rolling tower (s100)
- Available with wooden or fibre deck platforms
- The platform height is adjustable and this makes working at different working heights easy
- Maximum working height is 5.50 meters

PLATFORM HEIGHT (M)	2.2	3.2	4.2	5.2	6.2
---------------------	-----	-----	-----	-----	-----

- 1 m frame 75028-4
- 2m frame 75028-7
- Diagonal brace 245
- Horizontal brace 245
- Ladder hatch deck 245
- Clip-in ladder 3 m
- Clip-in ladder 4 m
- Clip-in ladder 5 m
- Castors wheel
- Toeboard set (0.75 - 2.45)
- Guardrail frame 75500-2
- Triangular stabiliser



Total Access
SOLUTIONS



Telephone: (02) 9524 6136

Fax: (02) 9524 9136

Email: info@totalaccesssolutions.com.au

get up • get in • get on